U.S. Officials Only CONFIDENTIAL

CENTRAL INTELLIGENCE AGENCY

INFORMATION REPORT

COUNTRY Angola

SUBJECT Porto Amboim, Port Information

PLACE ACQUIRED (BY SOURCE)

DATE ACQUIRED (BY SOURCE)

DATE (OF INFO.)

25X1A

OF THE UNITED STATES, MITHIN THE MEANING OF TITLE 18. SECTIONS 183 AND 794, OF THE U.S. CODE, AS AMENDED. ITS TRANSMISSION OR REVE-ATION OF ITS CONTENTS TO OR RECEIPT BY AN UNAUTHGRIZED PERSON LE ADMISSTED BY LAR. THE REPRODUCTION OF THIS REPORT IS PROMINITED.

KESPONSIAF IN 1 CD ND 00/C NO. ORR NO. CAS NO. OCI NO. & Apr 54 DATE DISTR.

NO. OF PAGES

NO. OF ENCLS.

SUPP. TO 25X1XREPORT NO.

SOURCE Officer of a US merchant ship.

 $/\overline{ ext{The}}$ Office of Naval Intelligence furnished the following information to CIA for IAC dissemination in accordance with paragraph 3c of NSCID #7. This information was obtained by DIO-3ND and was forwarded as ONI report 17-54.7

- General: Porto Amboim (Lat 10° 43' 51" S, Long 13° 44' 59" E) is a slight indentation in the coast of Angola on the West African coast. It is an open roadstead with no berthing facilities for ocean-going ships. Coffee for export, the main traffic in the port, is worked by lighters. The town of Amboim is small with about 30 houses and a few stores.
- Hydrography: The water off Porto Amboim is deep. It drops off suddenly 2. reaching a depth of 10 fathoms within 500 feet of the beach. The port can be approached from any direction from northwest through southwest. The outstanding landmark is a high bluff resembling a sugar-loaf on which a light is located. A recommended approach is to place the high bluff on a true bearing of 0900 and follow that heading. A small finger pier marked by red and green lights is situated near the base of the bluff.
- Lighterage: All cargo is worked by lighters, of which there are about six to eight with approximate capacities of 60 tons. As there are no towing craft in the port, the lighters must either be shifted by hand line or moved by ship's own craft. The source prefers the latter alternative and uses a motor lifeboat. When using the hand-line method, a ship should moor close to a buoy located 100 feet from the finger pier. A line runs from this buoy to the pier and by means of this lighters can be shuttled between ship and pier using lines handled by native labor.
- Pier: Built about May 1953, the finger pier is 75 feet long by about 25 feet wide. It is constructed of steel pilings with wooden decking and supports a small crane and a narrow gauge railway. The depth of water at its seaward end is about 30 feet, and although it is believed possible to bring a ship to the pier, it is dangerous and impractical because lighterage would still be required to work the ship's cargo. The pier is used to service lighters.
- Crane: The crane is an old steam-powered, railway lift of the derrick type and is capable of handling up to five tons. It is moved by native labor.

ONI DECLASSIFICATION/RELEASE INSTRUCTIONS ON FILE

U.S. Officia's Only

CONFIDENTIAL SEE LAST PAGE FOR SUBJECT & AREA CU.

													-
A POLLAGIUALSI	STATE	ARMY		NAVY	ì	ALR	FBI	_:					_
This re	port is for	the use	within th	ie USA	of the	Intelligence	compon	ents c	f the	Departr	nents	10	

Agencies indicated above. It is not to be transmitted overseas without the concurrence of the originalphof8vetarpsp release 2003/10/01 chcqasrdp805050509400050045017843 25X1A

Approved For Release 2003/10/01 : CIA-RDP80-00809A000500450178-3

CONFIDENTIAL/US OFFICIALS ONLY

-2-

25X1A

- 6. Railway: Two narrow gauge tracks running the length of the pier join into a single track leading the half-mile to the coffee warehouses. The rolling stock consists of several flat cars 10' by 4' and one small diesel engine.
- 7. Warehouses: Coffee for export is stored in three warehouses. These are of cement construction with clay tile roofing and are one story high, about 200 feet long by 75 feet wide.
- 8. Labor: Natives provide unskilled labor, while such skilled tasks as operating the crane and the railway are performed by Portugese labor. Ships provide their cwn stevedore manpower as a rule.
- 9. Communications: Porto Amboim is in telephone contact with Luanda and has telegraph lines to both Luanda and Lobito.
- Clearance Facilities: The primary average of communication with the outside world is the sea. No railroad is reported, and the only road is a poor road to Luanda which is not recommended for vehicles much larger than jeeps.

-ena-

CONFIDENTIAL/US OFFICIALS ONLY

LIBRARY SUBJECT & AREA CODES

756.548	:	1.7
756 . 545		1.2
756.543		1.2
756.549	:	12
756.544	1	1.2